

|                       |                                                   |                     |                                                                                                      |
|-----------------------|---------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------|
| SETTORE               | Tutti i settori escluso alimentare e farmaceutico | CERTIFICAZIONI      | EN 45545-2, NFPA 130, ISO 9001, TFL, cULus, CE, UKCA, IRIS, RoHS, Lloyd register, CURus, REACH, PADS |
| COMPATIBILITA' GUAINA | FPAS,FPAL,FPAH,FPASC,FPR,FPI,FPIH,FPIHRL          | GRADO DI PROTEZIONE | IP66, IP67,IP68,IP69                                                                                 |
| MATERIALE             | Nylon (PA66)                                      | NOTE                | /                                                                                                    |

| DIAMETRO ESTERNO | METRICO       | PG | NPT            | / |
|------------------|---------------|----|----------------|---|
| 13               | FPAU13-M16-90 |    |                |   |
| 16               | FPAU16-M16-90 |    | FPAU16-050-90B |   |
| 16               | FPAU16-M20-90 |    |                |   |
| 21               | FPAU21-M20-90 |    | FPAU21-050-90B |   |
| 28               | FPAU28-M25-90 |    | FPAU28-075-90B |   |
| 34               | FPAU34-M32-90 |    | FPAU34-100-90B |   |
| 42               | FPAU42-M40-90 |    | FPAU42-125-90B |   |
| 42               | FPAU42-M50-90 |    | FPAU42-150-90B |   |
| 54               | FPAU54-M50-90 |    | FPAU54-150-90B |   |
| 54               | FPAU54-M63-90 |    | FPAU54-200-90B |   |