

SETTORE	Tutti i settori escluso alimentare e farmaceutico	CERTIFICAZIONI	EN 45545-2, NFPA 130, Lloyd register, CURus, REACH, BSENIEC61386, CE, UKCA, RoHS
COMPATIBILITA' GUAINA	FPAS,FPAL,FPAH,FPASC,FPR,FPI,FPIH,FPIHRL,	GRADO DI PROTEZIONE	IP66
MATERIALE	Nylon (PA66)	NOTE	Indicato per colpi

DIAMETRO ESTERNO	METRICO	PG	NPT	/
10	FPA10-M12-90	FPA10-PG7-90		
11	FPA11-M12-90			
13	FPA13-M16-90	FPA13-PG9-90		
16	FPA16-M16-90	FPA16-PG9-90	FPA16-050-90	
16	FPA16-M20-90	FPA16-PG11-90		
16		FPA16-PG13-90		
18	FPA18-M20-90			
20	FPA20-M20-90			
21	FPA21-M20-90	FPA21-PG16-90	FPA21-050-90	
25	FPA25-M25-90	FPA28-PG21-90		
28	FPA28-M25-90		FPA28-075-90	
34	FPA34-M32-90	FPA34-PG29-90	FPA34-100-90	
42	FPA42-M40-90	FPA42-PG36-90	FPA42-125-90	
54	FPA54-M50-90	FPA54-PG48-90	FPA54-150-90	
54	FPA54-M63-90			
67	FPA67-M63-90	FPA67-PG48-90	FPA67-200-90	